

## **★ ISHIDA**



Typical system





Specifications	DACS-GN	DACS-GN-SE012 SS		DACS-GN-SE050 SS	
Weighing Compliance Requirements	Non MID	MID	Non MID	MID	
Weighing Capacity	1,250g	1,250g	5,000g	5,000g	
Upper Limit of Indication	1,254.5g	1,254.5g	5,018g	5,018g	
Lower Limit of Indication	8g	8g	32g	32g	
Actual Scale Interval (d)	0.05g	0.05g	0.2g	0.2g	
Verification Scale Interval (e)	N.A.	0.5g	N.A.	2g	
Max. Belt Speed	50 m/min (>=8g, <35g)		50 m/min (>=32g, <140g)		
	90 m/min (>=35g, <1,250g)		90 m/min (>=140g, <5,000g)		
Weight Conveyor Size	24: 220mm (V	24: 220mm (W) x 450mm (L)			
	35: 300mm (W) x 545mm (L)		- 35: 370mm (W) x 545mm (L)		
Ingress Protection	IP54		IP54		

Options	DACS-GN-SE012 SS	DACS-GN-SE050 SS	
CEIA (THS/SL-21E 3F) Metal Detector	✓	✓	
Safeline (Dual Frequency) Metal Detector	✓	✓	
STD Air Reject Option	✓		
HD Air (with reservoir) Reject Option	✓	~	
Arm Reject Option	✓	~	
Printer	✓	$\checkmark$	
IDCS Software and Hardware	✓	$\checkmark$	
Power Consumption	220-240V 50-60Hz	220-240V 50-60Hz	
Warranty Period	1 year	1 year	

Technical information is based upon information available at the time of print - 04/2019. Confirmation is provided during the Sales enquiry. Photographs and application shots may not be exact representations.

DACS-GN-SE

# Engineered to deliver performance with value

The Performance-Line checkweigher is suitable for a variety of product types and applications and has a simplified design for ease of use and setup.

- ▲ Front USB with approved encryption for the storage of production data
- ▲ 300 programmable pre-sets
- ▲ 7" LCD user keypad

Checkweighers

**Performance-Line Series** 

- ▲ Integrated Metal Detector option
- ▲ Automatic Reject options
- ▲ Supermarket Compliance Specification
- ▲ IP54 Rating



### Ishida Performance-Line Checkweighers

Every Ishida checkweigher system is configured and designed to suit the application. From a brandnew production line to integration into an existing one. Performance-Line Checkweighers can be configured to weigh only, weigh and reject, or incorporate a metal detector for a complete system. This can be further enhanced in accordance with Supermarket code of practice requirements.

#### Features & Benefits

#### **Reject Systems**

**Arm** - Ideal for boxes and bags. The non-compliant product is pushed off the side of the reject conveyor.

**Air Jet** - Suitable for small lightweight packaged products. The non-compliant product is blown off the side of the reject conveyor.

**HD** Air Jet - Suitable for medium-weight packaged products. The non-compliant product is blown off the side of the reject conveyor.

#### **Reject Bins & Roller Track**

**Reject Bins** - For holding rejected product. The bin is supplied with a lockable door.

**Gravity Roller Track** - For holding rejected product. Ideal for open trays and bulk boxes.

#### Weighing Flexibility

From the ability to utilise the checkweighers weigh data controls for other third party equipment to application specific software. The Performance-Line checkweigher can be built to a specification that meets production requirements.

#### Weight Compliance

Approved in accordance with WELMEC and OMIL Directives


#### Peace of Mind

Verifying and checking 100% products, the system helps support batch and regional weight compliance.

#### **Trusted Partner**

We developed our first checkweigher in 1975 and have continued to develop systems with the same level of quality and focus. All Ishida checkweighers contain our own developed and manufactured software, electronics and weigh cells.

#### Standard System



ISHIDA EUROPE LIMITED

Kettles Wood Drive Woodgate Business Park Birmingham B32 3DB United Kingdom Tel: +44 (0)121 607 7700 Fax: +44 (0)121 607 7888 info@ishidaeurope.com ISHIDA CZECH REPUBLIC Tel: +420 220 960 422

info@ishidaeurope.cz

#### ISHIDA ROMANIA

Tel: +44 (0)121 607 7700 Fax: +44 (0)121 607 7888 info@ishidaeurope.ro ISHIDA FRANCE Tel: +33 (0)1 48 63 83 83 Fax: +33 (0)1 48 63 24 29 info@ishidaeurope.fr

ISHIDA RUSSIA AND CIS Tel: +7 499 272 05 36 Fax: +7 499 272 05 37 info@ishidaeurope.ru ISHIDA GERMANY Tel: +49 (0)791 945 160 Fax: +49 (0)791 945 1699 info@ishida.de

#### ISHIDA SOUTH AFRICA Tel: +27 (0)11 976 2010 Fax: +27 (0)11 976 2012 info@ishidaeurope.com

ISHIDA MIDDLE EAST

Tel: +971 (0)4 299 1933 Fax: +971 (0)4 299 1955 ishida@ishida.ae

ISHIDA SWEDEN Tel: +46 (0)31 871 320 info@ishidaeurope.se

#### ISHIDA NETHERLANDS

Tel: +31 (0)499 39 3675 Fax: +31 (0)499 39 1887 info@ishida.nl

ISHIDA SWITZERLAND

Tel: +41 (0)41 799 7999 Fax: +41 (0)41 790 3927 info@ishida.ch