

**Multihead Weigher RVE Series** 




# **RVE Series**


## **CCW-RVE-210W-1S-30-SS/WP** CCW-RVE-214W-1S-30-SS/WP

## Robust, versatile & accurate weighing

Designed to handle a diverse range of free-flowing and semi-sticky products, this weigher can be adapted to suit many packaging scenarios. Configured in stainless steel finish or with enhanced water proof design, the RVE series is built for long life operations in dry, fresh or frozen applications.

- ▲ For dry, fresh or frozen product applications
- ▲ Mid to high speeds and excellent weighing yields
- ▲ Pre-configured for smart factories
- ▲ Achieves maximum speeds of up to 120wpm





Performance		CCW-RVE-210W-1S-30-SS/WP		CCW-RVE-214W-1S-30-SS/WP		
Max. weighing speed*		70 WPM		120 WPM		
Max. vol. for weighing (per single dump)		4.5 litres				
Max piece length		130mm				
Weighing capacity setting (per head)		400g	800g	400g	800g	
Minimum graduation		0.1g	0.2g	0.1g	0.2g	
Machine target weight range		15-500g	45-1000g	15-500g	45-1000g	
Specification	1					
Touch screen display (RCU)		10.4" Colour LCD Display				
Number of presets		200				
Weigh cell		Ishida double-beam strain gauge loadcell				
Materials		Surfaces are made of 304 stainless steel or other sanitary materials				
IP test rating		SS: IP54 Rating / WP: IP66 Rating				
Power	Wattage	0.7kW 1.7kW				
	Voltage	200-240V 50/60Hz 1-phase				
Air**		110 litre	110 litres/min (ANR) 0.5 Mpa Air hose - PT ³/s" (for air dryer connection) Air purge 0.02~0.03 Mpa			
Net weight***		Approx	Approx. 450kg		Approx. 550kg	
Standard Compliance			CE/FDA/RoHS			

Design and specifications are subject to change without notice (please confirm dimensions at point of order).

Depends on product shape, product density, target weight, feeding conditions, etc.

\* Compressed air supply is required only for WP machines. Note: Air hose compressor must be provided by user.

\*\* The machine weight varies depending on the options selected.



## **RVE Series**

Ishida has over 120 years history of weighing innovation, with more multihead weighers installed and adding value than any other supplier. The RVE series represents the latest in multihead weighing performance for speed, accuracy and reliability, and comes with a wide range of features to ensure high performance industrial weighing is achieved at a competitive price point.

## **Features & Benefits**

## Fast and precise weighing for improved productivity

High performance features include:

- ▲ Programmable 5 stage digital filtering
- ▲ Advanced automatic feeder adjustments
- ▲ High processing speed 10.4" web RCU

#### Increased yield and productivity

- Reduced giveaway and waste compared to conventional filling/weighing or semi-automated machines
- ▲ High processing capacity significantly improves production output
- ▲ Economical investment with a short payback period
- ▲ Contact part options to fit a wide range of solutions

## User-friendly design and easy set-up

Intuitive, easy-to-use RCU (Remote Control Unit)

- ▲ Simplifies initial set up and daily operations
- ▲ Minimises machinery downtime
- ▲ Maximises production efficiency
- ▲ USB data import/export with ethernet connectivity

#### Minimised machine downtime

- ▲ Tool-free, interchangeable contact parts reduces cleaning time
- ▲ Simple operation RCU screens are easy to learn and prevent operator errors

#### **Pre-configured for SMART FACTORIES**

- ▲ Increased productivity with Industry 4.0
- ▲ Sentinel™ Reporting Pack included free of charge
- ▲ Provides instant visibility of live machine performance from anywhere in the world
- ▲ Optional access to remote technical support, rapid response diagnosis and pro-active performance monitoring

### **Compliance with FDA and EU Food Contact standards**

All materials are FDA-approved and comply with Article 16(1) of Regulation (EC) No 1935/2004 and Article 15 of Regulation 10/2011. To fully meet the EU's Restriction of Hazardous Substances Directive (RoHS) non-hazardous materials are used for all circuit boards, parts, materials, and finishes.

United Kingdom Tel: +44 (0)121 607 7700 Fax: +44 (0)121 607 7888 info@ishidaeurope.com

#### ISHIDA CZECH REPUBLIC Tel: +420 220 960 422

Tel: +420 220 960 422 info@ishidaeurope.cz

## ISHIDA ROMANIA

Tel: +44 (0)121 607 7700 Fax: +44 (0)121 607 7888 info@ishidaeurope.ro

## ISHIDA FRANCE

Tel: +33 (0)1 48 63 83 83 Fax: +33 (0)1 48 63 24 29 info@ishidaeurope.fr

## ISHIDA RUSSIA AND CIS

Tel: +7 499 272 05 36 Fax: +7 499 272 05 37 info@ishidaeurope.ru

## ISHIDA GERMANY

Tel: +49 (0)791 945 160 Fax: +49 (0)791 945 1699 info@ishida.de

## ISHIDA SOUTH AFRICA

Tel: +27 (0)11 976 2010 Fax: +27 (0)11 976 2012 info@ishidaeurope.com

## ISHIDA MIDDLE EAST

Tel: +971 (0)4 299 1933 Fax: +971 (0)4 299 1955 ishida@ishida.ae

## ISHIDA SWEDEN

Tel: +46 (0)31 871 320 info@ishidaeurope.se

## ISHIDA NETHERLANDS

Tel: +31 (0)499 39 3675 Fax: +31 (0)499 39 1887 info@ishida.nl

## ISHIDA SWITZERLAND

Tel: +41 (0)41 799 7999 Fax: +41 (0)41 790 3927 info@ishida.ch