

**Multihead Weigher SE3 Series** 



# SE3 10 Heads


### CCW-SE3-210W-1S-20-PB/SS/WP


# High performance, cost effective weigher to improve productivity.

A reliable solution to automate the weighing of a wide variety of free flowing products. The simple construction makes this machine easy to use and clean whilst Ishida's high quality and weighing accuracy ensures minimum product giveaway with a short payback period. A simple menu-driven interface with up to 100 pre-sets offer rapid changeovers.

- ▲ Sanitary and easy-to-use solution
- ▲ For free flowing products and low target weights
- ▲ Achieves speeds of up to 70wpm

#### Dimensions





| Performance                              |         | CCW-SE3-210W-1S-20-PB/SS/WP  |      |
|--|---------|--|------|
| Max. weighing speed*                     |         | 70 WPM   |      |
| Max. vol. for weighing (per single dump) |         | 3 litres   |      |
| Max piece length                         |         | 95mm   |      |
| Weighing capacity setting (per head)     |         | 400g   | 800g |
| Minimum graduation                       |         | 0.1g   | 0.2g |
| Specification                            |         |  |      |
| Touch screen display (RCU)               |         | 10.4" Colour LCD Display   |      |
| Number of presets                        |         | 100  |      |
| Weigh cell                               |         | Double-beam loadcell   |      |
| Materials                                |         | Product surfaces are made of stainless steel or other sanitary materials         |      |
| IP test rating                           |         | PB + SS: IP-54 Rating / WP: IP-65 Rating   |      |
| Power                                    | Wattage | 0.8kW  |      |
|  | Voltage | 200-240V 50/60Hz 1-phase   |      |
| Air**                                    |         | 110 litres/min (ANR) 0.01-0.02 Mpa Air hose - PT 3/8" (for air dryer connection) |      |
| Net weight***                            |         | 350kg  |      |

Design and specifications are subject to change without notice (please confirm dimensions at point of order).

\*Depends on product shape, product density, target weight, feeding conditions, etc.

\*\*\* Compressed air supply is required only for WP machines. Note: Air hose compressor must be provided by user.

\*\*\* The machine weight varies depending on the options selected.



# SE3 10 Heads

Ishida has over 120 years history of weighing innovation, with more multihead weighers installed and adding value than any other supplier. The SE3 series offers high weighing accuracy at moderate speeds making it an ideal solution for growing companies.

#### Features & Benefits

#### Increased yield and productivity

- ▲ Reduced giveaway and waste compared to conventional filling/weighing or semi-automated machines
- ▲ High processing capacity significantly improves production output
- ▲ Economical investment with a short payback period
- ▲ Contact part options to fit a wide range of solutions

#### Consistent and accurate weighing results

High weighing accuracy features include:

- ▲ High power stepper motors
- ▲ Ishida double-beam strain gauge loadcell on each weigh hopper
- ▲ Dispersion table load cell sends feedback signal upstream to adjust infeed
- ▲ Digital Filtering and Digital Signal Processing

#### Easy set-up and operation

- ▲ Intuitive, easy-to-use RCU (Remote Control Unit)
- ▲ Up to 100 product presets reduces changeover time
- ▲ Ethernet option (data capture software and services)
- ▲ Multiple language software settings

#### Minimised machine downtime

- ▲ Tool-free, interchangeable contact parts reduces cleaning time
- ▲ Simple operation RCU screens are easy to learn and prevent operator errors

#### **Space saving**

The small footprint makes this an ideal solution for smaller or restricted factory spaces.

#### **Compliance with FDA and EU Food Contact standards**

All materials are FDA-approved and comply with Article 16(1) of Regulation (EC) No 1935/2004 and Article 15 of Regulation 10/2011. To fully meet the EU's Restriction of Hazardous Substances Directive (RoHS) non-hazardous materials are used for all circuit boards, parts, materials, and finishes.

#### Compliance







## ISHIDA EUROPE LIMITED

Kettles Wood Drive Woodgate Business Park Birmingham B32 3DB United Kingdom

Tel: +44 (0)121 607 7700 Fax: +44 (0)121 607 7888 info@ishidaeurope.com

# ISHIDA CZECH REPUBLIC

Tel: +420 317 844 059 Fax: +420 317 844 052 info@ishidaeurope.cz

#### ISHIDA ROMANIA

Tel: +40 (0)21 589 73 52 Fax: +40 (0)21 310 34 22 info@ishidaeurope.ro

#### ISHIDA FRANCE

Tel: +33 (0)1 48 63 83 83 Fax: +33 (0)1 48 63 24 29 info@ishidaeurope.fr

### ISHIDA RUSSIA AND CIS

Tel: +7 499 272 05 36 Fax: +7 499 272 05 37 info@ishidaeurope.ru

#### ISHIDA GERMANY

Tel: +49 (0)791 945 160 Fax: +49 (0)791 945 1699 info@ishida.de

#### ISHIDA SOUTH AFRICA

Tel: +27 (0)11 976 2010 Fax: +27 (0)11 976 2012 info@ishidaeurope.com

#### ISHIDA MIDDLE EAST

Tel: +971 (0)4 299 1933 Fax: +971 (0)4 299 1955 ishida@ishida.ae

#### ISHIDA SWITZERLAND

Tel: +41 (0)41 799 7999 Fax: +41 (0)41 790 3927 info@ishida.ch ISHIDA NETHERLANDS

Tel: +31 (0)499 39 3675 Fax: +31 (0)499 39 1887 info@ishida.nl